



OVERVIEW

The ACM Relay is a Wi-Fi module with 2 Relays and 2 dry inputs. It can be used to convert a traditional wall switch into a smart switch. It can control lights and shutters and can connect to the Internet to offer remote control via the TIS app.

KEY BENEFITS

- + Built-in Wi-Fi; links directly to the Internet
- + Control your lights and motorized curtains and shutters
- + Control your gate and locks
- + Keep the old installed switch and make it smart
- + Control by TIS app, locally or remotely

KEY FEATURES

- ★ 2 digital inputs (dry input)
- ★ Works with TIS-BUS Protocol
- ★ Small size; can be located anywhere and in any junction box



WIRELESS ACM RELAY

Wi-Fi Controller with 2 Dry Inputs

Models: ACM-2R-2Z



PRODUCT SPECIFICATIONS

⚡ Power supply	Input Voltage	110-230 VAC 50/60 Hz
	Output Power	3W / 12V
	Protection	Built in Protection fuse
	Current consumption	10-20 mA / 12 V DC
↑ Output	Number of relays	2
	Nominal voltage	110 / 230 V AC 50/60 Hz
	Nominal current per channel	3 A / 230 VAC
↑ Output switching current	Max switching current	3A/230 VAC Resistive 2A/230 VAC florescent
	Max Continues current	3A/230 VAC
	Max. switching Voltage	230VAC / 30VDC
↑ Output service life	Mechanical Endurance	> 10,000,000 OPS
↑ Output switching times	Operating time	8mS (at nomi. Volt)
	Releasing time	5mS (at nomi. Volt)
	Max. operating frequency	25 cycle/min
TIS AIR TIS AIR	WIFI Signal Protocol Standard	2.4 GHz 802.11 b/g/n
🔄 Reaction time		approx. 30ms
🔧 Mounting	Free locate	Can be installed anywhere
⬆️ Operating and display elements	Digital Inputs TIS AIR PRG Button with LED Upgrading	2 dry inputs for control ... TIS Protocol messages and commands Programming button and status LED. By WIFI Connection
⚖️ Weight	Without packaging	10 g
⊕ Dimensions	(Width × Length × Height)	49mm × 20mm × 49mm
📦 Housing	Materials Internal Parts color IP rating	PC fire proof White IP 50
🌡️ Temperature range	Operation	-10...60°C
	Storage	-20...50°C
	Transport	-25...75°C
💧 Air humidity		<80% non-condensing



Copyright © 2020 TIS, All Rights Reserved

TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.

TEXAS INTELLIGENT SYSTEM LLC
SUITE# 610, 860 NORTH DOROTHY DR
RICHARDSON
TX 75081,USA


TIS CONTROL LIMITED
RM 1502-p9 Easey CommBldg
253-261 Hennessy Rd Wanchai
Hong Kong

WIRELESS ACM RELAY

Wi-Fi Controller with 2 Dry Inputs

Models: ACM-2R-2Z

TIS
CONTROL EVERYTHING



Copyright © 2020 TIS, All Rights Reserved
TIS Logo is a Registered Trademark of Texas Intelligent System LLC in the United States of America. This company takes TIS Control Ltd. in other countries. All of the Specifications are subject to change without notice.

TEXAS INTELLIGENT SYSTEM LLC
SUITE# 610, 860 NORTH DOROTHY DR
RICHARDSON
TX 75081.USA

TIS CONTROL LIMITED
RM 1502-p9 Easay CommBldg
253-261 Hennessy Rd Wanchai
Hong Kong